

ASPEN



A cost effective rear wheel drive chair with a modular state-of-the-art design that provides improved obstacle climbing performance and an overall smoother ride. The Aspen is compatible with TB Flex rehab seating and electronics.

With its stylish, sleek design and a standard speed of up to 10 km/h, it's the ideal power chair for even the most active of clients.



QUANTUM®

#1 FOR REHAB POWER

f | quantumrehab.eu

Specifications

DRIVE WHEELS	14" pneumatic or flat free
CASTER WHEELS	9" solid
ANTI-TIP WHEELS	3" solid
SUSPENSION	Independent
MAXIMUM SPEED ¹	Up to 10 km/h
BRAKES	Intelligent brakes (electronic regenerative, disc park brake)
GROUND CLEARANCE ²	76 mm
TURNING RADIUS ²	430 mm
LENGTH ^{2,6}	1070 mm with front rigging 850 mm without front rigging
WIDTH ^{2,6}	580 mm
DRIVETRAIN	Two-motor, rear-wheel drive
SEATING SIZES	
SEATING SIZES ⁵	Width: 406 - 508 mm Depth: 406 - 508 mm
SEAT TO FLOOR HEIGHT ^{5,7,8,9}	420 mm (Low) 445 mm (Middle) 470 mm (High)
BATTERIES ³	Two 12 volt, deep-cycle NF-22, 62 Ah, AGM
BATTERY WEIGHT ⁵	18,7 kg each
RANGE PER CHARGE ^{1,4}	Up to 25 km
BATTERY CHARGER	8 Amp, off-board
AVAILABLE ELECTRONICS	Q-Logic or VR2
WEIGHT CAPACITY	136 kg
BASE WEIGHT WITHOUT BATTERIES ⁵	129,5 kg

1. Varies with base model, user weight, terrain type, battery Amp hour rating (Ah), battery charge, battery condition, motors, controller type, tire type, and tire condition. This specification is subject to a variance of +10%, -5%
2. Due to manufacturing tolerances and continued product improvement, this specification can be subject to a variance of (+ or -) 3%
3. AGM or Gel-Cell type required
4. Tested in accordance with ANSI/RESNA, WC Vol. 2, Section 4 & ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Test conducted at maximum weight capacity
5. Battery weight may vary based on manufacturer
6. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections
7. Seat-to-floor heights are measured with the unit unloaded
8. Tilt or lift adds 35 mm
9. Measurements without seat cushion

NOTE: All specifications subject to change without notice.

The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or - 3 %. Dimensions listed are for scooter only. Overall measurements will vary based on seating and accessory selections.

Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tire pressures, ambient temperature, and the gradient and surface of the road or pavement. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.

Features

- Rear-wheel drive design
- Stylish drive wheel rims
- Reflectors
- Audible free wheel alert system
- Low seat-to-floor heights
- Outstanding tight space manoeuvrability
- Narrow 580 mm width and compact 850 mm length (without front rigging)

Options

- Power tilt, recline, lift
- Front and rear turn signals and flashers
- Frame-mounted, base-integrated
- LED lighting system
- Unoccupied or occupied transit systems

Colours



Silver
Bullet



Electric
Blue



Back in
Black



Pride Mobility Products BV
De Zwaan 3, 1601 MS Enkhuizen
The Netherlands

Tel: +31 (0)85-0408630 · Fax: +31 (0)85-0430039
quantumrehab.eu · info@prideeurope.nl



PRIDE[®]
MOBILITY
LIVE YOUR BEST[®]

EU-SSQ0002/REVA/01 APR 22