

SPARKY





The Sparky is designed to deliver full rehab capability in a compact, powerful paediatric package. Engineered to operate in tight child-sized spaces and to keep up with today's active child, the Sparky is an exceptional fit from the playground to the classroom and beyond.



QUANTUM[®]

#1 FOR REHAB POWER

  | quantumrehab.eu

Specifications

DRIVE WHEELS	12" pneumatic
CASTOR WHEELS	8" pneumatic
ANTI-TIP WHEELS	3" solid
MAXIMUM SPEED ¹	Up to 10 km/h
GROUND CLEARANCE	95 mm
TURNING RADIUS ²	743 mm
OVERALL LENGTH ^{2,6}	95 mm
OVERALL WIDTH ^{2,6}	610 mm
STANDARD SEAT	Type: Sling Max size: 355 x 355 mm
BATTERY REQUIREMENTS	2x 40 Ah
BATTERY WEIGHT ^{3,5}	10,7 kg each
BATTERY CHARGER	5 Amp, off-board
AVAILABLE ELECTRONICS	VR2
RANGE PER CHARGE	Up to 25 km
SUSPENSION	Rear
BRAKING SYSTEM	Intelligent braking (electronic, regenerative disc brakes)
DRIVE TRAIN	Two-motor, rear-wheel drive
WEIGHT CAPACITY	56,7 kg
BASE WEIGHT	59,2 kg (without batteries)

1. Varies with base model, user weight, terrain type, battery amp hour rating (Ah), battery charge, battery condition, motors, controller type, tire type, and tire condition. This specification is subject to a variance of +10, - 5%.
2. Due to manufacturing tolerances and continued product improvement, this specification can be subject to a variance of +10, - 5%.
3. AGM or Gel-Cell type required. See VI. "Batteries and Charging."
4. Tested in accordance with ANSI/RESNA, WC Vol. 2, Section 4 & ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Test conducted at maximum weight capacity.
5. Battery weight may vary based on manufacturer.
6. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.

NOTE: All specifications subject to change without notice.

The information contained herein is correct at the time of publication; due to the manufacturer's commitment to constant improvement and development, they reserve the right to alter specifications without prior notice. Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressure, ambient temperature, and the gradient and surface of the road or pavement.

Features

- Fully adjustable seat - 250 mm x 250 mm through 355 x 355 mm
- PG VR2 Controller
- Power tilt
- Weight capacity up to 56,7 kg
- Maximum speed up to 10 km/h
- Swing-away footrests standard

Options

- Manual elevating leg rests
- Headrest
- Q-Logic drive controls
- Attendant control

Colours



White
Satin



Pride Mobility Products BV
De Zwaan 3
1601 MS Enkhuizen
The Netherlands

Tel: +31 (0)85-0408630 • Fax: +31 (0)85-0430039
quantumrehab.eu • info@prideeurope.nl



EU_SSQ0011/REVA/01DEC2020

