

MOTABILITY ID 721038

Q6 EDGE 2.0 WITH TB3 SEAT

DEALERS DETAILS

Dealers Name _____

Order Date _____

Address _____

Postcode _____

Phone _____ Email _____

PO No _____ Order Ref _____

DELIVERY DETAILS

Dealers Address _____

Postcode _____

Quantum Specialist _____

Ⓢ Clients Weight _____

BASE MODEL

- 13 Colour Options
- Height Adjustable Removable Armrests
- Centre Mount Foot Platform
- TB3 Seating
- 14" Flat Free Drive Tyres
- 2" x 6" Flat Free Front Castors



- 2" x 6" Flat Free Rear Castors
- ATX Suspension System
- NE+ Control System
- 2 x 62 ah Batteries
- 4 Mph (6 Km/h) Motors
- Max User Weight: 21 st 6lbs. (136 kg)

Standard = Standard Factory Feature
 FOC = Select Instead of Standard Factory Feature

DRIVE WHEELS

3" x 14" Flat Free Black Tyres. <i>With matching colour wheel accents.</i>	Standard
3" x 14" Pneumatic Black Tyres. <i>With matching colour wheel accents.</i>	FOC

COLOURS

Back in Black	Standard	White Satin*	FOC
Green Machine	FOC	Lemon Crush*	FOC
Midnight Blue	FOC	Night Train*	FOC
Electric Blue	FOC	Evolution Orange*	FOC
Pretty in Pink	FOC	Military Green*	FOC
Deep Purple	FOC	Grey Street*	FOC
Red Corvette	FOC		

* Extended lead-time.

Please download our free PQ-365 app to view colours and other product features in more detail.



SEAT PACKAGES - SEAT WIDTH

12"-16"W.
14"-16"W.
16"-20"W
20"-22"W
Set width at:

SEAT PACKAGES - SEAT DEPTH

12"-16"D.
14"-16"D.
16"-20"D
20"-22"D
Set depth at:

STEALTH SEAT CUSHIONS

No Seat Cushion Required	FOC
Simplicity G: General Use, Fluid Resistant Stealth-Tek Cover. <i>158.7 Kg weight limit.</i>	Standard
Zen SP: Skin Protection, 4-way Stretch, Coolcore Cover. <i>160 Kg weight limit.</i>	FOC
TRU-Comfort 2 SPP: Skin Protection, Positioning, 4-way Stretch Coolcore Cover. <i>158.7 Kg weight limit.</i>	FOC

Please note that seat cushions may not be available in all width and depth combinations. Refer to our Stealth Cushion Order Forms for size availability.

SEAT POSITIONING

Static Seat.	Standard
Static Seat to Floor Height. <i>From seat pan.</i>	16.5" 17.5" 18.5"

BACKREST SPECIFICATIONS

TRU-Balance 3 Back Support System. <i>Select TB3 back options below. Ignore all 'Back Cane' options.</i>	Standard
Back Canes Only System. <i>Not available with Power recline or TB3 flip-back arm supports. Move directly to 'Back Cane Only Support Options' if selected.</i>	FOC

Select one option above. Both options above include a metal active contour back support shell, TRU-Comfort 2 back cushion, and a set of wedge inserts.

TB3 BACK SUPPORT

Active Contour Back Support with TRU-Comfort 2 Back Cushion and Wedge Inserts. <i>Select size in Back Support Dimensions</i>	Standard
--	----------

TB3 BACK SUPPORT POSTIONING

TRU-Balance 3 Static Back. <i>Angle can be preset manually.</i>	Standard
TRU-Balance 3 Flip-forward Back. <i>Not available with TB3 flip-back arm supports, powered recline.</i>	FOC

BACK CANE ONLY SUPPORT

Active Contour Back Support with TRU-Comfort 2 Back Cushion and Wedge Inserts. <i>Select size in Back Support Dimensions.</i>	Standard
Back Cane Only Support Positioning. Tool Angle Adjustable. <i>85° to 120° in 5° increments.</i>	Standard
Back Cane Height. <i>From seat pan.</i>	16"H. 17"H. 18"H. 19"H. 20"H. 21"H. 22"H. 23"H. 24"H. 25"H.

BACK SUPPORT DIMENSIONS

Compatible with TB3 and Back Canes options above. Ignore Back Support Dimensions if omit back support is selected in TB3 or Back Canes sections. Back Support can be +/- 4" of seat width with TB3 Back Support System, but must be same as seat width with Back Canes Only System unless -2" or -4" Endo Mounts have been selected.

Backrest Support Width Package.		12"-14"W.	14"-16"W.	16"-20"W.
		18"-22"W.	20"-24"W.	
Back Support Width.	12"W.	14"W.	16"W.	17"W.
	18"W.	19"W.	20"W.	21"W.
	22"W.	24"W.		
Back Support Height. <i>From seat pan.</i>	14"H. <i>12"W back only.</i>	15"H. <i>12"W back only.</i>	16"H.	17"H.
	18"H.	19"H.	20"H.	21"H.
	22"H.	23"H.	24"H.	25"H. <i>Not available with 24"W back.</i>
	26"H. <i>Not available with 24"W back.</i>	27"H. <i>Not available with 24"W back.</i>	28"H. <i>Not available with 24"W back.</i>	29"H. <i>Not available with 24"W back.</i>

19" minimum backrest height when powered recline is selected.

ARM SUPPORTS

2-Post Flip-up Removable. <i>Adjustment range 9" to 13" from seat pan. Minimum seat depth 16".</i>	Standard	
Paediatric Single Post Drop-in Removable. <i>Adjustment range 7.75"- 9.75" from seat pan. 10" pads only.</i>	FOC	
Single Post Drop-in Removable. <i>Adjustment range 11"-17" from seat pan. Minimum seat depth 14".</i>	FOC	
TB3 Flip-back. <i>Adjustment range 8"-16" from seat pan. Includes lateral in/out adjustment.</i>	FOC	
Arm Support Pads.	10" Standard Standard 10" Waterfall. <i>Not with Std flip-up or TB Flex.</i>	FOC
	14" Standard FOC 14" Waterfall. <i>Not with Std flip-up or TB Flex.</i>	FOC

CENTRE MOUNTED LEG SUPPORTS

Base Mounted Flip-up Foot Platform. <i>Mounted to chassis. Will not move with powered lift or tilt.</i>	FOC	
Paediatric Adj. Centre Mount Foot Platform. <i>12"-14" seat widths only.</i>	FOC	
Manually Adjustable Centre Mount Foot Platform. <i>Minimum seat width 14".</i>	Standard	
Lower Leg Extensions. <i>From seat pan.</i>	8"-12". <i>Paediatric centre mount only.</i> FOC 10"-16". Standard 13"-19". FOC	
Footplates.	10"W x 6"D Split Footplates. <i>Paediatric centre mount only.</i>	FOC
	10"W x 8"D Split Footplates. FOC 10"W x 11"D Split Footplates.	Standard
Calf Support.	Individual Calf Pads. <i>6"W x 6"H.</i>	Standard

INDIVIDUALLY MOUNTED LEG SUPPORTS

70° Swing-Away Leg Supports. <i>Flip-up footplates. Adj. range 12" to 15". Minimum seat width 15".</i>	FOC
90° Paediatric Swing-Away Leg Supports. <i>4"W x 6"D angle & depth adj. footplates. Adjustment range 7" to 11".</i>	FOC
Manual Elevating Swing-Away Leg Supports. <i>Flip-up footplates. Adj. range 15" to 20". Min. seat width 15".</i>	FOC

INDIVIDUALLY MOUNTED CONFIGURABLE LEG SUPPORTS

60° to 90° Tool Adjustable Swing-Away Supports. <i>Flip-up extruded footplates 8.5"W x 6"D. Select lowers below. Minimum seat width 15".</i>	FOC
Lower Leg Extensions. <i>From seat pan.</i>	11"-13" FOC 13.5"-16.5" Standard 15.5"-19.5" FOC

Certain configurations may result in reduced ground clearance below footplates. Contact Quantum Technical for information. Adjustment ranges above are from seat pan to footplates. Individual legrests are supplied with heel loops.

STEALTH HEAD SUPPORTS

UniLink 8" Comfort Plus. <i>HMO475-17M / CP08CCFPM.</i>	FOC
UniLink 10" Comfort Plus. <i>HMO475-17M / CP10CCFPM.</i>	FOC
UniLink 14" Comfort Plus. <i>HMO475-17M / CP14CCFPM.</i>	FOC

Please visit stealthproducts.com for alternative head supports.

PELVIC BELTS

Auto Buckle Lap Belt, Push Button Release.	Standard
--	----------

NON-EXPANDABLE CONTROLS

NE + Controls. <i>With no power options.</i>	Standard	
Control Method.	Hand Control. <i>Select position in Hand Control Mounts below.</i>	Standard
	Attendant Control. <i>Hand control mounted at rear.</i>	FOC

HAND CONTROL MOUNTS

Fixed.	Standard	
Swing-away. <i>Swings in & out with height, tension and pivot adjustment.</i>	FOC	
Mounting Position.	Left	Right

SPEED PROGRAM & LIGHTS PACKAGE

4 Mph Program with Lights and indicators.	Standard
6 Mph Program with Lights and indicators.	FOC

ACCESSORIES

Prepare Chassis for Dahl Docking System. <i>Dahl system not included.</i>	FOC
---	-----

NOTES & SPECIAL REQUESTS



Quantum®
 32 Wedgwood Road, Bicester,
 Oxon, OX26 4UL
 Phone: 01869 324600
 Fax: 01869 323070
 Email: sales@quantumrehab.co.uk
 Web: www.quantumrehab.co.uk
MOTABILITY ID 721038 - 14/04/23 V1



Crash Tested



V1: 14/06/2022

